

DC BATTERY BACKUP BELT DRIVE LED WIFI® GARAGE DOOR OPENER CORNER TO CORNER LIGHTING[™] MAKES THE ENTIRE GARAGE BRIGHT





880RGDW

Integrated Battery Backup Powers up the opener when the power's out.

POWERFUL ADD-ONS:

Automatic Garage Door Lock Capable Deadbolts the garage door automatically every time it closes.



Remote Light Control Plug in any lamp to this device to control it with a smartphone or garage remote.



Compact and portable to provide quick,



Wireless Keyless Entry Provides convenient, secure access from outside the garage with a 4-digit PIN.



Mini Universal Remote Control

easy garage access.

WLEDRGD

CORNER TO CORNER LIGHTING WITH LONG-LASTING LEDS DELIVERS 3,100 LUMENS OF DAYLIGHT-LIKE LIGHTING TO THE ENTIRE GARAGE SPACE.

AUTOMATIC GARAGE DOOR LOCK CAPABLE DEADBOLT LOCKS THE GARAGE DOOR, MAKING IT VIRTUALLY IMPENETRABLE (2 MAX., SOLD SEPARATELY).

TIMER-TO-CLOSE CAN BE PROGRAMMED TO CLOSE THE DOOR AFTER A SET AMOUNT OF TIME.

SECURITY+ 2.0° SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK[®] ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

MOTION DETECTOR LIGHTS THE WAY AUTOMATICALLY.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

AND RELIABLE

BELT DRIVE SYSTEM AND QUIET DC MOTOR PROVIDE SMOOTH OPERATION AND LONG-LASTING SERVICE.

SOFT START/STOP FOR SMOOTH OPERATION.

BATTERY BACKUP ENSURES GARAGE ACCESS EVEN WHEN THE POWER'S OUT.

WARRANTY LIFETIME MOTOR, 5-YEAR PARTS, 1-YEAR BATTERY AND ACCESSORIES.

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

MYQ MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE. *Linking your myQ account to a partner may require an additional accessory purchase or subscription

General[™] II with WiFi[®] **DC Battery Backup Belt Drive**



MASTERFUL ENGINEERING.

MOTOR

- 12V DC
 - 53 RPM
 - Automatic Thermal Protection
 - Permanent Lubrication
- 120V AC
 60 Hz Voltage

POWER

- 2.7A Current Rating
- UL[®] Listed
- 6' Power Cord (3-Prong)

MECHANICS

- Steel Chassis, T-Rail and Trolley
- Full Reinforced Belt Drive Mechanism (63:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- Electronic Limits for Easy Setup
- DC WiFi[®] Logic Board with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050DCTWFLK)
- **2 Lock Terminals** Allow up to 2 Locks to Be Connected (Sold Separately)

STANDARD SPECS.

SECURITY+ 2.0° RADIO CONTROLS I^{Operating Range:} ~200

Operating Temperature: -40°F to 150°F

- 3-Button Remote Control (893RGX):
- Remote Control: 310, 315 and 390 MHz Tri-Band*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding

Tri-Band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster openers manufactured since January 1993.

ENCRYPTED CONTROLS

- Smart Control Panel® (880RGDW)
 - Timer-to-Close
 - Program Remote Controls, Keypads and myQ Accessories

HFAD

RAII

- Maintenance Alert System
- Easy WiFi[®] Setup

SHIPPING.

SHIPPING WEIGHT (in lbs.)

CARTONS (3)

- CARTON 1: 19.81" x 11.94" x 11.19"
- Garage Door Opener Head (WLED) with Integrated Battery Backup (485LM)
- Smart Control Panel (880RGDW)
- 3-Buttom Remote Control (893RGX)
- The Protector System[®] Safety Reversing Sensors
- CARTON 2: 10'4" x 5" x 5" (for 7' Rail)
- Assembled Solid-Steel Chain T-Rail
- CARTON 3 (OPTIONAL): 8" x 4.5" x 4"
- Automatic Garage Door Lock (841LG)



MyQ° RADIO

((C 902–928 MHz)) 50-Channel FHSS

(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and myQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK[®] COMPATIBLE

(VERSION 4.0 OR HIGHER**)

**May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.



DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	125"	140"	164"
Max. Opening	7'6"	8'6"	10'6"
Headroom Clearance Required: 2"			

for door to move upward 6.5"

QII

Per second

Per second for door to move downward

LIGHTING

- 2 LED Light Panels
- 100 Points of LED Light
- 3,100 Lumens, ***
- 4,000 Kelvin
- Light Temperature

Ш

- Adjustable Time
- Disabled in Battery Backup Mode
- ***Verified by an independent lab.

SAFETY AND SECURITY.

- Automatic Garage Door Lock Capable (2 Max.)
- Alert 2-Close/Unattended Close Operation⁺
- Motion Detection Feature on Control Panel
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
 Safety Beam
 Obstruction Turns
 Lights On
- Maintenance Alert
- System - Garage Door Opener Capacity
 - of up to 40 Remote Controls,
- 4 Wireless Keyless Entry
- Systems and 16 myQ Devices

 ${\rm tWARNING}$ to reduce the risk of injury to persons- ONLY enable Timer-to-Close and myQ remote operation features when opener is installed on a sectional door.



econtri comp HOMELI)3. (VERSIO **May require model and ye

3

AUTOMATIC

DOOR LOCK

(OPTIONAL)

GARAGE