

DC BATTERY BACKUP BELT DRIVE LED WiFi® GARAGE DOOR OPENER CORNER TO CORNER LIGHTING™ MAKES THE ENTIRE GARAGE BRIGHT



KEY FEATURES

- ULTRA-BRIGHT Lighting
- QUIET Operation
- POWER-OUTAGE Performance
- WI-FI Built In

BATTERY BACKUP
CALIFORNIA SB-969
COMPLIANT

SECURE

CORNER TO CORNER LIGHTING WITH LONG-LASTING LEDS DELIVERS 3,100 LUMENS OF DAYLIGHT-LIKE LIGHTING TO THE ENTIRE GARAGE SPACE.

AUTOMATIC GARAGE DOOR LOCK CAPABLE DEADBOLT LOCKS THE GARAGE DOOR, MAKING IT VIRTUALLY IMPENETRABLE (2 MAX., SOLD SEPARATELY).

TIMER-TO-CLOSE CAN BE PROGRAMMED TO CLOSE THE DOOR AFTER A SET AMOUNT OF TIME.

SECURITY+ 2.0* SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

MOTION DETECTOR LIGHTS THE WAY AUTOMATICALLY.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

QUIET AND RELIABLE

BELT DRIVE SYSTEM AND QUIET DC MOTOR PROVIDE SMOOTH OPERATION AND LONG-LASTING SERVICE.

SOFT START/STOP FOR SMOOTH OPERATION.

BATTERY BACKUP ENSURES GARAGE ACCESS EVEN WHEN THE POWER'S OUT.

WARRANTY LIFETIME MOTOR, 5-YEAR PARTS, 1-YEAR BATTERY AND ACCESSORIES.

SMART

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

MYQ MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.

* Linking your myQ account to a partner may require an additional accessory purchase or subscription fee. ** Controlling this HomeKit-enabled accessory automatically and away from home requires an Apple TV* with tvOS™ 10.0 or later or an iPad* with iOS 10.0 or later set up as a home hub. † Requires additional purchase of myQ Home Bridge 819LMB. Smartphone not included. Application screens may vary. Cellular data or WiFi connection required. Test equipment regularly and follow safety instructions.

INCLUDED ACCESSORIES:

Smart Control Panel®

LCD display enables simple programming and adjustment of settings.



6080959

880RGDW

3-Button Remote Control

Operates up to 3 openers or MyQ Light Accessories.



2220178

893RCX

Integrated Battery Backup

Powers up the opener when the power's out.



6080759

485LM

POWERFUL ADD-ONS:

Automatic Garage Door Lock Capable

Deadbolts the garage door automatically every time it closes.



6080989

841LC

Remote Light Control

Plug in any lamp to this device to control it with a smartphone or garage remote.



2220174

825 LM

Mini Universal Remote Control

Compact and portable to provide quick, easy garage access.



2220185

374UT

Wireless Keyless Entry

Provides convenient, secure access from outside the garage with a 4-digit PIN.



2220166

877MAX

MASTERFUL ENGINEERING.

MOTOR

- 12V DC
- 53 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER

- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL® Listed
- 6' Power Cord (3-Prong)

MECHANICS

- **Steel Chassis, T-Rail and Trolley**
- **Full Reinforced Belt Drive Mechanism** (63:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **DC WiFi® Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050DCTWFLK)
- **2 Lock Terminals** Allow up to 2 Locks to Be Connected (Sold Separately)

7.5"



19"

10.5"

DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	125"	140"	164"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

9"

Per second for door to move upward

SPEED

6.5"

Per second for door to move downward

STANDARD SPECS.

SECURITY

SECURITY+ 2.0®

RADIO CONTROLS

Operating Range: ~200'

Operating Temperature: -40°F to 150°F

3-Button Remote Control (893RGX):

- Remote Control: 310, 315 and 390 MHz Tri-Band*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding

*Tri-Band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

ENCRYPTED CONTROLS

Smart Control Panel® (880RGDW)

- Timer-to-Close
- Program Remote Controls, Keypads and myQ Accessories
- Maintenance Alert System
- Easy WiFi® Setup

SMART

MyQ® RADIO



50-Channel FHSS
(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and myQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK® COMPATIBLE

(VERSION 4.0 OR HIGHER**)

**May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING



- 2 LED Light Panels
- 100 Points of LED Light
- 3,100 Lumens, *** 4,000 Kelvin Light Temperature
- Adjustable Time
- Disabled in Battery Backup Mode

***Verified by an independent lab.

SHIPPING.

SHIPPING WEIGHT (in lbs.)

CARTONS (3)

- Garage Door Opener Head (WLED) with Integrated Battery Backup (485LM)
- Smart Control Panel (880RGDW)
- 3-Button Remote Control (893RGX)
- The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5" (for 7' Rail)

- Assembled Solid-Steel Chain T-Rail

CARTON 3 (OPTIONAL): 8" x 4.5" x 4"

- Automatic Garage Door Lock (841LG)

22
HEAD

17
RAIL

3
AUTOMATIC GARAGE DOOR LOCK (OPTIONAL)

SAFETY AND SECURITY.

- Automatic Garage Door Lock Capable (2 Max.)
- Alert 2-Close/Unattended Close Operation†
- Motion Detection Feature on Control Panel
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 40 Remote Controls, 4 Wireless Keyless Entry Systems and 16 myQ Devices



†WARNING: to reduce the risk of injury to persons- ONLY enable Timer-to-Close and myQ remote operation features when opener is installed on a sectional door.