

3/4 HP AC CHAIN DRIVE WIFI® GARAGE DOOR OPENER

RELIABLE AND SECURE WITH THE CONVENIENCE OF BUILT-IN WIFI.



WARRANTY

LIFETIME
Motor

5-YEAR
Parts

1-YEAR
Accessories

RELIABLE

SMART

SECURE

P3
MOTORS®

3/4 HP AC MOTOR CHAIN DRIVE SYSTEM IS BUILT TO PROVIDE MAXIMUM POWER TO LIFT THE HEAVIEST DOORS INCLUDING CARRIAGE HOUSE AND SOLID WOOD.

I-BEAM RAIL SYSTEM AND REINFORCED CHASSIS WITH CHAIN DRIVE PROVIDES MAXIMUM SUPPORT.



FREE MyQ MOBILE APP SO USERS KNOW THEIR HOME IS SECURE.

BUILT-IN WIFI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

REAL-TIME ALERTS INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

Security+ 2.0®

SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

TIMER-TO-CLOSE AUTOMATICALLY CLOSE THE DOOR AFTER A PRE-PROGRAMMED NUMBER OF MINUTES .

MOTION DETECTOR PROVIDES RAPID DETECTION AND ILLUMINATION OF GARAGE.

INCLUDED ACCESSORIES:

Smart Control Panel®

Provides easy programming of remotes, keypads, MyQ accessories and Wi-Fi Garage Door Openers.



6080959

880RCDW

3-Button Remote Control

Operates up to 3 openers or MyQ Light Accessories.



2220178

893RCX

POWERFUL ADD-ONS:

Automatic Garage Door Lock Capable

Deadbolts the garage door automatically every time it closes.



6080989

841LC

Remote Light Control

Enables home lighting control through a garage remote or a smartphone.



2220174

825LM

Garage Door and Gate Monitor

Monitors and closes up to 4 garage doors from any room in the house.



2220175

829LM

Mini Universal Remote Control

Compact and portable to provide quick, easy garage access.



2220185

374UT

MASTERFUL ENGINEERING.

MOTOR

- ¾ Horsepower
- 1,625 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER

- 120V AC
- 60 Hz Voltage
- 5A Current Rating
- UL Listed
- 6' Power Cord (3-Prong)

MECHANICS


- **Steel Chassis, T-Rail and Trolley**
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **Solid State Micro-controller** with Built-In Surge Suppressor



DIMENSIONS

Rail Options	7'	8'	10'	12'	14'
Installed Length	125"	140"	164"	189"	213"
Max. Opening	7'6"	8'6"	10'6"	12'6"	13'6"

Headroom Clearance Required: 2"



STANDARD SPECS.

SECURITY

SECURITY+ 2.0*

RADIO CONTROLS

3-Button Remote Control
Operating Range: ~200'

- Operating Temperature: -40°F to 150°F
 Frequency:
- Remote Control: 310, 315 and 390 MHz Tri-Band
 - Garage Door Opener: Frequency Agile on 310, 315, 390 MHz
 - Security+ 2.0 Anti-Burglary Coding

SECURITY +2.0 ENCRYPTED CONTROLS

- Smart Control Panel*
- Timer-to-Close
 - Program Remote Controls, Keypads, WiFi Garage Door Openers & MyQ Accessories
 - Maintenance Alert System

SMART

MyQ® RADIO

902-928 MHz
 50-Channel FHSS

(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables remote closing of garage door with key MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING



- Max. 2 100-Watt Light bulbs
- Adjustable Time
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts

ENERGY EFFICIENCY

- Approximately 1 Watt Power in Standby mode*
- *Occurs at Down Limit When opener's Lights Turn Off

SHIPPING.

SHIPPING WEIGHT (in lbs.)



CARTONS (2)

CARTON 1: 20" x 12" x 10"

- Smart Control panel
- 3-Button Remote Control
- Garage Door Opener Head
- The Protector System® Safety Reversing Sensors
- Chassis Support Bracket
- Safety Sensor Extension Brackets

CARTON 2: 10'4" x 5" x 5"

- Assembled Solid-Steel I-Beam (Chain)

CONVENIENCE AND SAFETY.

- The Protector System® Safety Reversing Sensors
- Alert-2-Close/Unattended Close Operation†
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 24 Remote Controls, 2 Wireless Keyless Entry Systems and 16 MyQ Devices
- PosiLock® Secure Lock System



HomeLink® and the HomeLink House® logo are registered trademarks of Genetex Corporation

†: To reduce the risk of injury to persons, only use alert-2-Close/Unattended Close Operation features when installed with a sectional door.