

3/4 HP AC CHAIN DRIVE WIFI® GARAGE DOOR OPENER

RELIABLE AND SECURE WITH THE CONVENIENCE OF BUILT-IN WIFI.



WARRANTY

LIFETIME
Motor

5-YEAR
Parts

1-YEAR
Accessories

P3
MOTORS®

3/4 HP AC MOTOR CHAIN DRIVE SYSTEM IS BUILT TO PROVIDE MAXIMUM POWER TO LIFT THE HEAVIEST DOORS INCLUDING CARRIAGE HOUSE AND SOLID WOOD.

I-BEAM RAIL SYSTEM AND REINFORCED CHASSIS WITH CHAIN DRIVE PROVIDES MAXIMUM SUPPORT.



FREE MyQ MOBILE APP SO USERS KNOW THEIR HOME IS SECURE.

BUILT-IN WIFI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

REAL-TIME ALERTS INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

Security+ 2.0®

SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

TIMER-TO-CLOSE AUTOMATICALLY CLOSE THE DOOR AFTER A PRE-PROGRAMMED NUMBER OF MINUTES .

MOTION DETECTOR PROVIDES RAPID DETECTION AND ILLUMINATION OF GARAGE.

INCLUDED ACCESSORIES:

Smart Control Panel®

Provides easy programming of remotes, keypads, MyQ accessories and Wi-Fi Garage Door Openers.



6080959

880RCDW

3-Button Remote Control

Operates up to 3 openers or MyQ Light Accessories.



2220178

893RCX

POWERFUL ADD-ONS:

Automatic Garage Door Lock Capable

Deadbolts the garage door automatically every time it closes.



6080989

841LC

Remote Light Control

Enables home lighting control through a garage remote or a smartphone.



2220174

825LM

Garage Door and Gate Monitor

Monitors and closes up to 4 garage doors from any room in the house.



2220175

829LM

Mini Universal Remote Control

Compact and portable to provide quick, easy garage access.



2220185

374UT

RELIABLE

SMART

SECURE

MASTERFUL ENGINEERING.

MOTOR

- ¾ Horsepower
- 1,625 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER

- 120V AC
- 60 Hz Voltage
- 5A Current Rating
- UL Listed
- 6' Power Cord (3-Prong)

MECHANICS


- **Steel Chassis, T-Rail and Trolley**
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **Solid State Micro-controller** with Built-In Surge Suppressor



DIMENSIONS

Rail Options	7'	8'	10'	12'	14'
Installed Length	125"	140"	164"	189"	213"
Max. Opening	7'6"	8'6"	10'6"	12'6"	13'6"

Headroom Clearance Required: 2"



STANDARD SPECS.

SECURITY

SECURITY+ 2.0*

RADIO CONTROLS

3-Button Remote Control
Operating Range: ~200'

- Operating Temperature: -40°F to 150°F
 Frequency:
- Remote Control: 310, 315 and 390 MHz Tri-Band
 - Garage Door Opener: Frequency Agile on 310, 315, 390 MHz
 - Security+ 2.0 Anti-Burglary Coding

SECURITY +2.0 ENCRYPTED CONTROLS

- Smart Control Panel*
- Timer-to-Close
 - Program Remote Controls, Keypads, WiFi Garage Door Openers & MyQ Accessories
 - Maintenance Alert System

SMART

MyQ® RADIO

902-928 MHz
 50-Channel FHSS

(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables remote closing of garage door with key MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING



- Max. 2 100-Watt Light bulbs
- Adjustable Time
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts

ENERGY EFFICIENCY

- Approximately 1 Watt Power in Standby mode*
- *Occurs at Down Limit When opener's Lights Turn Off

SHIPPING.

SHIPPING WEIGHT (in lbs.)



CARTONS (2)

CARTON 1: 20" x 12" x 10"

- Smart Control panel
- 3-Button Remote Control
- Garage Door Opener Head
- The Protector System® Safety Reversing Sensors
- Chassis Support Bracket
- Safety Sensor Extension Brackets

CARTON 2: 10'4" x 5" x 5"

- Assembled Solid-Steel I-Beam (Chain)

CONVENIENCE AND SAFETY.

- The Protector System® Safety Reversing Sensors
- Alert-2-Close/Unattended Close Operation†
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 24 Remote Controls, 2 Wireless Keyless Entry Systems and 16 MyQ Devices
- PosiLock® Secure Lock System



HomeLink® and the HomeLink House® logo are registered trademarks of Genetex Corporation

†: To reduce the risk of injury to persons, only use alert-2-Close/Unattended Close Operation features when installed with a sectional door.